

Model 9300 Weight Indicator

- 6-digit display
- 100,000 display graduations
- Powers up to 8 load cells
- 15 Updates/second typical
- NEMA 4 stainless steel washdown enclosure
- Selectable primary/secondary units lb, kg, ounces, short tons, metric tons, grams or none
- 2 independent serial communication ports: (1) full duplex, (1) unidirectional or active 20 mA current loop
- Full front-panel digital calibration & configuration
- Three-stage digital filtering
- CE marked



SPECIFICATIONS

ELECTRICAL	
Excitation Voltage	10 ±0.5VDC, 8 x 350Ω load cells or 16 x 700Ω load cells
PERFORMANCE	
Maximum Display Counts	100,000
Analog Signal Input Range	0.6 mV/V - 4.5 mV/V
Sensitivity	0.3µV/graduation min.
Measurement Rate	15 measurements/second
ENVIRONMENTAL	
Operating Temperature	14 to 122°F -10 to 50°C
POWER	
AC Power	±2.0 115 or 230 VAC 50-60 HZ
MECHANICAL	
Weight	6.4 lb (2.9 kg)
Enclosure	NEMA 4X/IP66 Stainless steel
Enclosure Size	9.5 in x 6 in x 2.75 in
Display	6 digit LED

OPTIONS

Analog output: selectable 0-10V, 4-20 mA
 Panel mount kit
 Please specify if CE mark is required